

TECHNICAL DOCUMENT

AD PROTECT, ORANGE

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

AD PROTECT ORANGE flooring oil suitable for oil finishing of wooden floors. Good filling properties, natural colour, good chemical and mechanical resistance. Give the floor a satined aspect . The durability can be improved by adding the hardener 5 UA% (optional)

TECHNICAL DATA

VISCOSITY +/- 35-45 SEC. (DIN 4mm/20°C)

SOLID CONTENTS +/- 51% by weight

DENSITY +/- 0,91 kg/l

GLOSS mat

COLOUR naturel

PREPARATION

The surface needs to be clean and dry.

USER TIPS

Before use, shake and stir well. Can be applied by paintbrush, polishing machine, roller or cloth.

After applying the oil, the excess has to be wiped off or buffed in with a white pad.

DRYING TIME

AD PROTEC ORANGE can be over-coated after 6 to 8 hours.

The drying time is strongly depending on the applied quantity, the temperature and the ventilation room. Through a higher temperature and a good ventilation, drying time is reduced.

APPLYING QUANTITY

+/- 35 m² / liter

AFTER TREATMENT

Clean regular with flooring soap.

ATTENTION : The hardwaxoil needs +/- 14 days to fully cure. Do not use any water or maintenance products on the floor during this period.

OTHER

Used cloths need to be thrown into water after use, because of the danger of spontaneous combustion.

As with all wood finishing always do a test area first to safeguard against an undesirable outcome. This technical data sheet is merely a guide and not a guarantee. All product are formulated to the best of our knowledge. The information is given as a result of many years experience. This product has had extensive tests carried out.